TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010–QUARTO-(NA)-ITALY
TAL.+ 39 – 081 – 876.21.48 r.a. - FAX + 39 – 081 – 876.23.47
http://www.dichemitaly.com E-mail: dichem@dichemitaly.com

NITROFAST EC

CODE : 30.340 WHITE GLOSS — **CODE : 30.320 BLACK GLOSS**
CODE : 30.330 WHITE MAT — **CODE : 30.310 BLACK MAT**

DESCRIPTION	Fast drying nitrocellulose enamel; Main characteristics: High build, fast drying, available in gloss or semi-mat version.
PURPOSE	Nitrocellulose enamel suitable for painting industrial equipment or commercial vehicles.
COLOURS	White – black. Others available upon request.
COVERAGE THEORETICAL	**BASIC DATA (At 25 deg. C - 50 % R. H.)** 8 – 9 sqm/mixed litre
THINNER	**Dinitril**
DILUTION : 70 %	**Nitrofast gloss /mat** 100 **Dinitril :** 70

APPLICATION METHOD	This product is primarily intended for application by: Conventional air-spray, airless spray
AIR SPRAY APPLICATION	Pressure 2,5 – 3 bar Nozzle 1,5 - 2 mm Dry film thickness 40-50 um Number of coats 2 - 3 **(Ensure clean, water-free air supply)**
DRYING TIMES AT 20°C	Dustfree after 10 min. Trought dry after 12 hours
STORAGE	24 months (stored in a cool dry place away from direct sunlight).
PACKAGING	0,75 and 4 litres.
CARTON	12 x 0,75 - 4 x 4.

Our technical department is at your service for any further details or information you may require.